

Medium Thermal Fleece Blanket (UNHCR Standard)



FLAME
RETARDANT



ROT
PROOF



Specifications

Material	Synthetic blankets knitted or woven, dry raised both sides, 100% virgin polyester on dry weight, ISO1833
Tensile Strength	250 N warp and weft minimum, ISO13934-1
Shrinkage & Weight Loss	Maximum 5% warp and weft, ISO6330
Thermal Resistance	TOG 2.5 minimum (ISO5085-1) with thickness 3 mm minimum (ISO5084)
Resistance to Air Flow	Maximum 1000 L/m2 /s under 100 Pa pressure drop, ISO9237
Finish	Whipped seam at 10 mm from the edge with 10 to 13 stitches/10 cm or stitched ribbon or hemmed on 4 sides
Organoleptic Test	No bad smell, not irritation, no dust, pH between 4 and 9, free from harmful VOC (Volatile Organic Components), fit for human use
Fire Resistance	Resistance to cigarette (ISO12952-1&2) Resistance to flame (ISO12952-3&4)

Medium Thermal Fleece Blanket

Dimensions

Size

150 x 200 cm +3% / -1%

Weight

350 to 450 g/m² ± 20g

Packing / Shipping

Bale Dimension

80 x 52 x 47 cm (20 pieces per water tight bale)

Weight

25 kg approx (per bale)

Loading with Pallets

20' 2240 blankets | 40' 4800 blankets per | HCL 4800 blankets

Loading without Pallets

20' 3220 blankets | 40' 6800 blankets per | HCL 7500 blankets

For more
information visit
nizamcanvas.com