



LEIF TENT

(UNHCR Standard — Eco Design)



WATER
PROOF



UV
STABILISED



FLAME
RETARDANT



ROT
PROOF



15% RECYCLED
CONTENT

Two Doors (Front & Rear) + Two Full-Length Side Windows + Ridge Ventilation + One Chimney Reinforcement | Sewn-In Tub Ground Sheet.

Specifications

Fabric	Outer Tent: 170 GSM (+/-10%) Woven High-Density Polyethylene, Black Core Fibres With White LDPE Coating Both Sides — Up To 15% Post-Consumer Recycled Content. Flame Retardant (EN 13823-A1).
	Inner Tent: 130 GSM Polyester Cotton — Flame Retardant (CPAI 84-6, MI + B2).
	Ground Sheet & Mud Flap: 170 GSM (+/-10%) Woven PE. Sewn-In Tub Construction.
	Mosquito Netting: Polyester, PVC Coated.

Colour	Outer Tent White Inner Tent Sand / Cream
--------	--

Accessories	Complete With Metal Poles, Hammer, Pegs, Ropes, Pins, Repair Kit, Assembly Instruction, Etc
-------------	---

Dimensions

Length x Width	6.60 x 4.00 Meter
Total Floor Area	23 m2
Vestibule Area	7 m2 2 x 3.50 m2
Center Side Wall Height	2.20 1.25 Meter
Door Height	1.40 Meter
Length x Width Inner Tent	3.95 x 3.80 Meter
Center Side Wall Height	2.10 1.15 Meter
Weight	49 Kg
Capacity	5 Persons



LEIF TENT (UNHCR STANDARD)

Features & Construction

Doors

Outer Tent: 2 Doors (130 x 140 cm), One Front + One Rear.
Inner Tent: 2 Doors (100 x 175 cm), One Front + One Rear.

Windows

Outer Tent: 2 Long Side Windows (360 x 60 cm) + 2 Ventilation Openings, Front And Rear.
Inner Tent: 2 Windows Of Equal Size.

Ventilation

1 Full-Length Ridge Vent + 2 Upper Gable Vents On Inner Tent.

Chimney

1 Heat-Resistant Chimney Reinforcement In Both Inner And Outer Tent.

Frame & Pegs

Poles

1 Ridge Pipe 4.00 m | 2 Upright Poles 2.20 m | 6 Side Poles 1.25 m | 4 Door Poles 1.40 m

Pegs

6 T-Pegs (25 x 25 x 3 mm) 40 cm | 4 Candy-Cane Pegs 30 cm | 26 O-Pegs 23 cm

Performance & Characteristics

Life Span	Min. 3 Years, All Climates
Shelf Life	Min. 5 Years, Warehouse
Set-Up	Approx. 20 Min 3 Persons
Fungal Resistance	Not Sensitive To Fungi
Weight	49 Kg

Treatments

Core Treated With UV Stabilisers. No Harmful Chemical Surface Treatments.

Packing

Packing Unit

Tent In A PE Bag With Separated Webbing Bands + Handle. 1 Piece Per Unit.

Contents

Outer Tent, Inner Tent With Ground Sheet, Poles, Accessories And Hammer.

Packing / Shipping

Dimensions | Weight | Volume Packed

230 x 30 x 30 cm 49 Kg 0.21 Cbm

Dimensions | Weight | Pallet Volume

230 x 120 x 113 cm 805 Kg 3.20 Cbm

Packed Qty on a Pallet

16 Units Per Metal Stackable Pallet

Loading

20' DC 180 Units Loose | 160 Units Palletised
40' DC 340 Units Loose | 320 Units Palletised
40' HC 360–400 Units Loose | 320 Units Palletised

Marking

On Request

Optional Accessories

- Winterization Kit
- Shade Net
- Logo Printing



SUSTAINABILITY

Recycled Materials

Outer tent woven with up to 15% post-consumer recycled polyethylene.

Treatments

Flame-retardant additives are embedded into the yarn during manufacture. No phosphorus-based FR additives and no chemical surface treatments.

Packaging

Sustainable materials, designed for a second life. No unnecessary single-use plastics.

Transport

Packaging, pallet build and container loading are optimised.

Durability

Long-life materials selected to extend service life in the field.

Repair

Field repairable. Supplied with a repair kit.

Second Life

Designed so materials can be re-purposed after service.

Marking

Printed with water-based ink on sustainable sticky tape.



For more
information visit
nizamtents.com